


### RAW MATERIAL TECHNICAL DATA

COD.	<b>GQ 15 PW-PG-BF</b>	
ITEM DESCRIPTION	QUADRA GUIDE 15x15	
BASE RAW MATERIAL	Polyvinyl Chloride and Nitrilic Rubber ( <b>PVC /NBR</b> )	
CO-EXTRUSION RAW MATERIAL		

### BELT TECHNICAL DATA

Data	Value	U.M	Tolerance
Size/Diameter	15x15	mm	*+/- 0,2
Hardness	63	Sh A	*+/- 3
Color/Masterbatch	<b>Pure White-Petrol Green-Blu Food</b>		
Food Approvment	FDA/EC		SI
Weight	Weight per lenght	Kg/ml	0,300
Specification			
Reinforcing Cord		mm	
Surface Finishing	Matte		
Temp. Min	Min. Working Temp in continuous	°C	- 20
Temp. Max	Max. Working Temp in continuous	°C	+ 50
Conveying side trasversal	Min. pulley diameter	mm	80
Conveying side longitudinal	Min. pulley diameter	mm	200
Running side	Min. pulley diameter	mm	140
Tensile Force	Tensile Force for 5% elongation	N	
Friction Coeff.	On steel pulleys		0,45

### BELT PACKAGING / APPLICATIONS

Roll Lenght	75	ML	
Roll Weight	22,5	KG	
Application	Conveyor's guide		
Joining	Hot welding - High Frequency Welding		
Characteristics	Elastic belt, Flexibility, easy welding - <b>OIL RESISTANT</b>		

All rights reserved. No part of this publication may be reproduced. Distributed, or transmitted in any form or by any means, including photocopyng, recording, or other electronic or mechanical metthods, without tthe prior written permission of 4-belt srl.