


RAW MATERIAL TECHNICAL DATA

| | | |
|---------------------------|--|---|
| COD. | GQU 10 PW-BG-BF |  |
| ITEM DESCRIPTION | QUADRA GUIDE 10x10 | |
| BASE RAW MATERIAL | Aromatic Thermoplastic Polyurethane (TPU) | |
| CO-EXTRUSION RAW MATERIAL | | |

BELT TECHNICAL DATA

| Data | Value | U.M | Tolerance |
|-----------------------------|--|-------|-----------|
| Size/Diameter A x B | 10x10 | mm | *+/- 0,2 |
| Hardness | 83 | Sh A | *+/- 3 |
| Color/Masterbatch | Pure White-Britain Green-Blu Food | | |
| Food Approvment | FDA/EC | | SI |
| Weight | Weight per lenght | Kg/ml | 0,130 |
| Specification | | | |
| Reinforcing Cord | | mm | |
| Surface Finishing | Smooth | | |
| Temp. Min | Min. Working Temp in continuous | °C | - 20 |
| Temp. Max | Max. Working Temp in continuous | °C | + 50 |
| Conveying side trasversal | Min. pulley diameter | mm | 60 |
| Conveying side longitudinal | Min. pulley diameter | mm | 140 |
| Running side | Min. pulley diameter | mm | 120 |
| Tensile Force | Tensile Force for 5% elongation | N | |
| Friction Coeff. | On steel pulleys | | 0,40 |

BELT PACKAGING / APPLICATIONS

| | | | |
|-----------------|--|----|--|
| Roll Lenght | 150 | ML | |
| Roll Weight | 19,5 | KG | |
| Application | Conveyor's guide | | |
| Joining | Hot welding - High Frequency Welding | | |
| Characteristics | Elastic belt, Flexibility, easy welding - OIL RESISTANT | | |

All rights reserved. No part of this publication may be reproduced. Distributed, or transmitted in any form or by any means, including photocopyng, recording, or other electronic or mechanical metthods, without tthe prior written permission of 4-belt srl.