


RAW MATERIAL TECHNICAL DATA

COD.	GQU 8 PW-BG-BF	
ITEM DESCRIPTION	QUADRA GUIDE 8X8	
BASE RAW MATERIAL	Aromatic Thermoplastic Polyurethane (TPU)	
CO-EXTRUSION RAW MATERIAL		

BELT TECHNICAL DATA

Data	Value	U.M	Tolerance
Size/Diameter	8X8	mm	*+/- 0,2
Hardness	83	Sh A	*+/- 3
Color/Masterbatch	Pure White-Britain Green-Blu Food		
Food Approvment	FDA/EC		SI
Weight	Weight per lenght	Kg/ml	0,080
Specification			
Reinforcing Cord		mm	
Surface Finishing	Smooth		
Temp. Min	Min. Working Temp in continuous	°C	- 20
Temp. Max	Max. Working Temp in continuous	°C	+ 50
Conveying side trasversal	Min. pulley diameter	mm	50
Conveying side longitudinal	Min. pulley diameter	mm	130
Running side	Min. pulley diameter	mm	100
Tensile Force	Tensile Force for 5% elongation	N	
Friction Coeff.	On steel pulleys		0,40

BELT PACKAGING / APPLICATIONS

Roll Lenght	200	ML	
Roll Weight	16	KG	
Application	Conveyor's guide		
Joining	Hot welding - High Frequency Welding		
Characteristics	Elastic belt, Flexibility, easy welding - OIL RESISTANT		

All rights reserved. No part of this publication may be reproduced. Distributed, or transmitted in any form or by any means, including photocopyng, recording, or other electronic or mechanical metthods, without tthe prior written permission of 4-belt srl.